



## Lifting Eye Starpoint RUD VRS-F

### Product information



Star shaped design, can be adjusted to the direction of pull. Higher load capacities than DIN 580-Eyebolts

**Material:** Forged high tensile engineering steel, crack detekted.

**Marking:** According to standard, WLL

**Finish:** Striking fluorescent pink powder coating

**Standard:** EN 1677-1

**Safety factor:** 4:1

Part Code	Code	WLL ton	Thread	WLL straight lift ton	Eye diam.Ø mm	Thread Length mm	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	N mm	T mm	Weight kg	Total price
06.VRS-FM08	VRS-F	0.3	M8	1	25	12	11	9	25	25	30	16.3	47	12	6	35	0.12	N/A
06.VRS-FM10	VRS-F	0.4	M10	1	25	15	11	9	25	25	30	16.3	47	15	6	35	0.12	N/A
06.VRS-FM12	VRS-F	0.75	M12	2	30	18	13	10	30	30	34	19.8	56	18	8	42	0.21	N/A
06.VRS-FM16	VRS-F	1.5	M16	4	35	24	15	13	35	36	40	-	65	24	10	49	0.36	N/A
06.VRS-FM20	VRS-F	2.3	M20	6	40	30	17	16	40	41	50	-	76	30	12	58	0.6	N/A
06.VRS-FM24	VRS-F	3.2	M24	8	49	36	20	19	49	51	60	35	92	36	14	70	1.05	N/A
06.VRS-FM30	VRS-F	4.5	M30	12	60	45	26	24	60	66	75	44	114	45	17	87	2.08	N/A
06.VRS-FM36	VRS-F	7	M36	16	73	54	32	29	73	76	98	53	135	54	22	104	3.49	N/A
06.VRS-FM42	VRS-F	9	M42	24	84	63	37	33	84	86	111	62	158	63	24	121	5.4	N/A
06.VRS-FM48	VRS-F	12	M48	32	94	72	42	42	94	100	128	70	180	72	27	138	8.17	N/A

# Blueprint

