

Crane Scale Dynafor™ LLZ2



Product information



Wireless digital dynamometer

Specifications :

- Capacity range from 1t up to 250t
- Radio-Frequency 2.4GHz chipset for wireless range up to 400m with Tractel® Dynafor HDD, large displays AL128 & AL63, DMU and software accessories
- Bluetooth chipset for a connection to any smartdevice equipped with our free app', up to 30m
- Both Bluetooth and Radio-Frequency 2.4 GHz available
- 0.2% accuracy of full scale
- Powered by 3 AA batteries
- IP 65

Temperature range: -20°C up to +50°C.

Safety factor: 4:1.

Part Code	WLL ton	Model	Test load tons	Increment kg	Resolution 0.3% FS ± kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg	Delivery time
423500100050	1	LLZ2 1t	1.5	1	3	191	164	22	83,5	22	19,8	36,4	37,6	0.75	7
423500320050	3.2	LLZ2 3.2t	4.8	5	9.6	191	164	22	99.5	22	19,8	36,4	44.8	0.93	7
423500630050	6.3	LLZ2 6.3t	9.6	10	18.9	236	184	28	121.5	22	19,8	36,4	54.7	1.44	7
423501250050	12.5	LLZ2 12.5t	18.75	20	37.5	277	226	42	120.5	45	40,5	59.4	60,0	3.22	7
423502000050	20	LLZ2 20t	30	50	60	342	264	54	147	45	40,5	59.4	73.5	4.95	7

Blueprint

