


## Steel Wire Rope 6x19S-FC

### Product information



ISO 4309 Rope category No: All Diameters RCN.02

... [Read more](#)




**Rope construction:** 6x19S-FC  
**Marking:** According to standard  
**Standard:** EN 12385-4

**Fill factor:** 0.49  
**RCN:** 02

Slings



Overhead cranes



Tower crane



## Steel Wire Rope 6x19S-FC

### Technical data

Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
101100304270170	3	1,960	Galvanized	sZ	5.42	3.21	Dry	3.11
101100403270170	4	1,960	Galvanized	zS	9.63	5.71	Dry	5.54
101100504270170	5	1,960	Galvanized	sZ	15	8.93	Dry	8.65
101100604270170	6	1,960	Galvanized	sZ	23.1	13.8	Dry	13
101100704270170	7	1,960	Galvanized	sZ	31.7	18.8	Dry	18
101100804270170	8	1,960	Galvanized	sZ	41.4	24.6	Dry	23
101101004270170	10	1,960	Galvanized	sZ	64.7	38.4	Dry	36