

Ferrule T Talurit®



Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for fibre core single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and spiral strand ropes.

Material: Aluminum

Marking: According to standard

Standard: EN 13411-3

except size range

Note: See the manufacturer's product data sheet in the tab "Documents" for guidance on dimension selection.

Part code	Ferrule size mm	Length mm
120100300020	3	14
120100350020	3.5	16
120100400020	4	18
120100450020	4.5	20
120100500020	5	23
120100600020	6	27
120100650020	6.5	29

120100700020	7	32
120100800020	8	36
120100900020	9	40
120101000020	10	45
120101100020	11	50
120101200020	12	54
120101300020	13	59
120101400020	14	63
120101600020	16	72
120101800020	18	81
120102000020	20	90
120102200020	22	99
120102400020	24	108
120102600020	26	117
120102800020	28	126
120103000020	30	135
120103200020	32	144
120103400020	34	153
120103600020	36	162
120103800020	38	171
120104000020	40	180
120104400020	44	198
120104200020	42	189

120104600020	46	207
120105000020	50	225
120105400020	54	243