

Eye / Eye Crosby HG-226

Product information



End fittings are quenched and tempered, bodies heat treated by normalizing. Turnbuckle eyes are forged elongated, by design, to maximize easy attachment in system and minimize stress in the eye. For turnbuckle sizes 6 mm through 64 mm, a shackle one size smaller can be reeved through eye.

Standard: According to Federal Specifications FF-T-791b.

... [Read more](#)

Marking: Logo, size and type.


Finish: Hot dipped galvanized.

Note: Turnbuckles recommended for straight or in-line pull only.

Safety factor: 5:1

Eye / Eye Crosby HG-226

Blueprint



Technical data

Part code	WLL ton	Thread dia. & take up inch	A mm	J open mm	K closed mm	M open mm	N closed mm	R mm	S mm	X closed mm	BB mm	Weight kg
422100540100	0.54	3/8 x 6	9.53	446	294	463	311	28.7	13.5	62.9	155	0.34
422100100100	1	1/2 x 6	12.7	506	354	529	376	35.8	18	90.4	153	0.78
422100450107	4.54	1 x 6	25.4	666	514	711	559	76.2	36.3	165	157	4.36
422100450105	4.54	1 x 12	25.4	971	666	1,016	711	76.2	36.3	165	309	5.88