



## Bolt Type Anchor Shackle Crosby G-2130

### Product information

Bolt Type Anchor shackles with thin head bolt - nut with cotter pin. Meets the performance requirements of Federal Specification RR-C 271G Type IVA, Grade A, Class 3, except for those provisions required of the contractor.

**Proof load:** 2 x WLL.

**Material:** Forged – Quenched and Tempered, with alloy bolts

**Marking:** According to standard, CE-marked, WLL, RFID chip for 25T and higher.

**Temperature range:** -40°C up to +204°C

**Finish:** Galvanized with painted bolt.

**Standard:** EN 13889

**Safety factor:** 6:1

**Grade:** 6

Part code	WLL ton	Size inch	A mm	B mm	C mm	D mm	E mm	F mm	H mm	L mm	M mm	N mm	A Tolerance +/-	C Tolerance +/-	Weight kg
420100030250	0.33	3/16	9,7	6,4	22,4	4,9	15,2	14,2	37,3	24,9	32,8	4,85	1,50	-	0.03
420100050250	0.5	1/4	11,9	7,9	28,7	6,4	19,8	15,5	46,7	32,5	39,6	6,35	1,50	1,50	0.05
420100080250	0.75	5/16	13,5	9,7	31,0	7,9	21,3	19,1	53	37,3	46,2	7,85	1,50	1,50	0.1
420100100250	1	3/8	16,8	11,2	36,6	9,7	26,2	23,1	63,0	45,2	55,1	9,65	1,50	1,5	0.15
420100150250	1.5	7/16	19,1	12,7	42,9	11,2	29,5	26,9	74,0	51,5	63,8	11,2	1,50	3,30	0.22
420100200250	2	1/2	20,6	16,0	47,8	12,7	33,3	30,2	83,5	58,5	71,1	12,7	1,50	3,30	0.36
420103500250	35	2	82,5	57,0	197	51,0	146	122	348	253	275	61	3,30	6,35	23.7
420105500250	55	2-1/2	105	70,0	267	66,5	184	145	453	327	345	79,5	6,35	6,35	44.6
420108500250	85	3	127	82,5	330	76,0	200	165	546	365	384	92	6,35	6,35	69.9
420112000250	120	3-1/2	133	95,5	372	92,0	229	203	626	419	432	105	6,35	6,35	120

# Blueprint

