

## Alloy Bolt Type Shackle Crosby G-2130A



### Product information

**Design:** Bolt Type Anchor shackles with thin head bolt – nut with cotter pin. Meets the performance requirements of Federal Specification R-C-271G, Type IVA, Grade B, Class 3, except for those provisions required of the contractor.

**Material:** Forged Alloy Steel – Quenched and Tempered, with bow and bolt.

**Marking:** According to standard, CE-marked, WLL.

**Finish:** Hot dip galvanized.

**Standard:** DNV 2.7-1 Approved

**Safety factor:** 8

**Grade:** 8

| Part code    | WLL ton | Size inch | A mm | B mm | C mm | D, mm | E mm | F mm | H, mm | L mm | Mmm mm | Nmm mm | A Tolerance +/- mm | C Tolerance +/- mm | Weight kg |
|--------------|---------|-----------|------|------|------|-------|------|------|-------|------|--------|--------|--------------------|--------------------|-----------|
| 420100200240 | 2       | 1/2       | 20.6 | 16   | 47.8 | 12.7  | 33.3 | 30.2 | 83.5  | 58.5 | 71.1   | 12.7   | 1.5                | 3.3                | 0.36      |
| 420100330240 | 3.25    | 5/8       | 26.9 | 19.1 | 60.5 | 16    | 42.9 | 38.1 | 106   | 74.5 | 90.4   | 17.5   | 1.5                | 6.35               | 0.62      |
| 420100480240 | 4.75    | 3/4       | 31.8 | 22.4 | 71.5 | 19.1  | 51   | 46   | 126   | 89   | 105    | 20.6   | 1.5                | 6.35               | 1.23      |
| 420100650240 | 6.5     | 7/8       | 36.6 | 25.4 | 84   | 22.4  | 58   | 53   | 148   | 102  | 122    | 24.6   | 1.5                | 6.35               | 1.79      |
| 420100850240 | 8.5     | 1         | 42.9 | 28   | 95.5 | 25.4  | 68.5 | 60.5 | 167   | 119  | 137    | 26.9   | 1.5                | 6.35               | 2.28      |
| 420100950240 | 9.5     | 1-1/8     | 46   | 31.8 | 108  | 28.7  | 74   | 68.5 | 190   | 131  | 150    | 31.8   | 1.5                | 6.35               | 3.75      |
| 420101200240 | 12      | 1-1/4     | 51.5 | 35.1 | 119  | 31.8  | 82.5 | 76   | 210   | 146  | 170    | 35.1   | 1.5                | 6.35               | 5.31      |
| 420101350240 | 13.5    | 1-3/8     | 57   | 38.1 | 133  | 35.1  | 92   | 84   | 233   | 162  | 183    | 38.1   | 3.3                | 6.35               | 7.17      |
| 420101700240 | 17      | 1-1/2     | 60.5 | 41.4 | 146  | 38.1  | 98.5 | 92   | 254   | 175  | 196    | 41.1   | 3.3                | 6.35               | 8.62      |

## Blueprint

