

## Alloy Bolt Type Shackle Crosby G-2130A



### Product information

**Design:** Bolt Type Anchor shackles with thin head bolt – nut with cotter pin. Meets the performance requirements of Federal Specification R-C-271G, Type IVA, Grade B, Class 3, except for those provisions required of the contractor.

**Material:** Forged Alloy Steel – Quenched and Tempered, with bow and bolt.

**Marking:** According to standard, CE-marked, WLL.

**Finish:** Hot dip galvanized.

**Standard:** EN 13889, DNV 2.7-1 Approved

**Safety factor:** 8

**Grade:** 8

Part Code	WLL ton	Nominal Size (in.)	A mm	B mm	C mm	D mm	E mm	F mm	H mm	L mm	M mm	N mm	A Tolerance +/-	C Tolerance +/-	Weight kg	Delivery time
420100200240	2	1/2	20.6	16	47.8	12.7	33.3	30.2	83.5	58.5	71.1	12.7	1.5	3.3	0.36	3
420100330240	3.25	5/8	26.9	19.1	60.5	16	42.9	38.1	106	74.5	90.4	17.5	1.5	6.35	0.62	3
420100480240	4.75	3/4	31.8	22.4	71.5	19.1	51	46	126	89	105	20.6	1.5	6.35	1.23	3
420100650240	6.5	7/8	36.6	25.4	84	22.4	58	53	148	102	122	24.6	1.5	6.35	1.79	3
420100850240	8.5	1	42.9	28	95.5	25.4	68.5	60.5	167	119	137	26.9	1.5	6.35	2.28	3
420100950240	9.5	1-1/8	46	31.8	108	28.7	74	68.5	190	131	150	31.8	1.5	6.35	3.75	3
420101200240	12	1-1/4	51.5	35.1	119	31.8	82.5	76	210	146	170	35.1	1.5	6.35	5.31	3
420101350240	13.5	1-3/8	57	38.1	133	35.1	92	84	233	162	183	38.1	3.3	6.35	7.18	3
420101700240	17	1-1/2	60.5	41.4	146	38.1	98.5	92	254	175	196	41.1	3.3	6.35	8.62	3

## Blueprint

