

Lifting Eye TAPG/TAPG-S

Product information



The TAPG and TAPG-S screw-on attachment point is a rotatable lifting point designed for industrial lifting, assembly, and transport applications. Available both with and without fastening screw, it provides flexible integration for machinery, fabricated structures, and equipment requiring a defined lifting connection.

Best used for:

- Machinery, steel fabrications, and industrial equipment.
- Applications requiring a compact rotating lifting point.
- Installations needing either supplied or customer-selected screws.

Product benefits:

- Rotatable lifting ring supports improved load alignment.
- Available with or without screw for installation flexibility.
- Compact bolt-on design integrates easily into equipment.
- Suitable for multi-directional industrial lifting applications.
- Defined WLL capacities support clearer lifting planning.

Model TAPG: Lifting D-Ring and Bridge - without Screws.

Model TAPG-S: Lifting D-ring, bridge and 2 screws 8.8 EN 24014 (DIN 931) [... Read more](#)

Material: Eye of alloy steel.

Marking: CE-marked, UKCA-marked, WLL.

Note: The surface that the lifting eyes shall be attached to shall be flat and tolerate the load it is going to be exposed to.

Warning: Only screws with a minimum strength class of 8.8 EN 24014 (DIN 931) may be used

Safety factor: 4:1

