



Lifting Eye APS

Product information

Advantages:

- Compact design
- Secured four times against breakage
- D-link swings 180°
- Weld-on shackle made of material S355JR according to EN 10025
- Also loadable transversely to the swivel direction

Material: Eye of alloy steel. Welding attachment of steel St 52.

Marking: CE-marked, WLL.

Finish: Painted.

Note: The surface that the lifting eyes shall be attached to shall be flat and tolerate the load it is going to be exposed to.

Safety factor: 4:1

Part Code	Code	WLL ton	a mm	b mm	c mm	ø d mm	e mm	f mm	l mm	Weight kg	Delivery time
4215381701000	TAPS 1	1.12	32	38	32	13	25	70	42	0.32	7
4215381702000	TAPS 2	2	34	40	34	14	26	72	42	0.33	7
4215381703000	TAPS 3	3.15	47	56	50	18	36	92	54	0.84	7
4215381705000	TAPS 5	5.3	55	67	60	22	46	111	63	1.56	7
4215381708000	TAPS 8	8	68	80	68	26	54	127	68	2.62	7
4215380415000	TAPS 15	15	82	125	100	30	60	190	120	5.4	7

Technical data

kind of attachment	□	□	□	□	□	□		
number of piece	1	1	2	2	2	3 o. 4		
inclination angle	0°	90°	0°	90°	0°-45°	45°-60°	0°-45°	45°-60°
Code	WLL ton							
t	t	t	t					

Blueprint

