

## Snatch Block McKissick 419 with Shackle - Light Champion

## **Product information**

The McKissick snatch block 419 Light Champion from Crosby is a snatch block fittled with a shackle. Available from WLL 2 up to 15 T. Can be delivered with bronze bushing (BB) and from WLL 8 T also with roller bearing (RB).

## Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Material: Forged steel.
Marking: CE-marked

Safety factor: 4:1

| Part Code    | Code      | Rope Ø range<br>mm | WLL<br>ton | Sheave dia.<br>mm | Bearing Code | A<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | H<br>mm | Weight<br>kg | Delivery time |
|--------------|-----------|--------------------|------------|-------------------|--------------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 424100200200 | 419 w/eye | 8-10               | 2          | 76                | ВВ           | 220     | 76      | 67      | 168     | 14      | 14      | 35      | 35      | 1.8          | 3             |
| 424100400200 | 419       | 10-13              | 4          | 114               | ВВ           | 340     | 108     | 79      | 268     | 16      | 18      | 43      | 51      | 5.4          | 3             |
| 424101500206 | 419       | 22-26              | 15         | 457               | ВВ           | 842     | 460     | 129     | 559     | 38      | 44      | 79      | 78      | 72.1         | 3             |
| 424101500207 | 419       | 22-26              | 15         | 457               | RB           | 841     | 460     | 129     | 565     | 38      | 44      | 79      | 79      | 72.1         | 7             |

## Blueprint

