

Steel Wire Rope 6x36WS-IWRC

Product information



ISO 4309 Rope Category No: All Diameters **RCN.09**

Rope construction: 6x36WS-IWRC.

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.59

RCN: 09

Slings




Winch rope



Stay rope



Overhead cranes



Tower crane



Container crane



Mobile port crane



Offshore crane



Loading crane



Crawler crane



Piling crane



Ladle crane




STS crane



Straddle carrier



RTG



Part Code	Rope Diameter,	Steel area mm ²	Min. Breaking force kN. 1960 N/mm ²	Min. Breaking force kN. 1770 N/mm ²	Weight kg/100m
101100804270231	8	29.4	44.7	-	26.2
101100904050231	9	37.3	-	51	33.1
101101004050231	10	46	69.8	63	40.9
101101204270231	12	66.2	100	-	58.9
101101304270231	13	77.7	118	-	69.1
101101404270231	14	90.2	137	-	80.2
101101604270231	16	118	179	-	105
101101804270231	18	149	226	-	133
101101904270231	19	166	252	-	148
101102004050231	20	184	279	252	164
101102204270231	22	223	338	-	198
101102404270231	24	265	402	-	236
101102604270231	26	311	472	-	276
101102804270231	28	361	547	-	321

101103004270231	30	414	628	-	368
101103204270231	32	471	715	-	419
101103404270231	34	532	807	-	473
101103604270231	36	596	904	-	530
101103804270231	38	664	1008	-	591
101104004270231	40	736	1120	-	654
101104203270231	42	811	1231	-	721
101104404270231	44	891	1351	-	792
101104804270231	48	1,060	1608	-	942
101105204270231	52	1,244	1887	-	1,106
101105604270231	56	1,443	2188	-	1,283