Lifting Solutions Group
Axel Johnson International

Carabiner Pulley ROLLCLIP A, Petzl

Product information



Pulley-carabiner that facilitates installation of the rope when pulley is connected to the anchor

ROLLCLIP A is a pulley-carabiner with a gate opening on the pulley side that facilitates installation of the rope when the pulley is fixed to the anchor. It is available with an automatic TRIACT-LOCK locking system, or without a locking system. ROLLCLIP A may be used with a CAPTIV positioning bar to favor loading of the carabiner along the major axis, to limit the risk of it flipping and to keep it integrated with the device.

- Min. rope diameter: 7 mm
- Max. rope diameter: 13 mm
- Sheave diameter: 18 mm
- Maximum working load: 2 x 2 = 4 kN
- Efficiency: 85 %
- Major axis strength: 20 kN
- Minor axis strength: 8 kN
- Open gate strength: 7 kN

... *Read more*

Material: Aluminum
Marking: According to standard, CE-marked, UKCA-marked
Standard: EN 362, EN 12278

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Carabiner Pulley ROLLCLIP A, Petzl

Technical data

Part code	Min. breaking force kN	Rope Ø mm	Locking device*	Weight kg
823500800951	8	7-13	Non-locking	0.105
823500800950	8	7-13	TRIACT-LOCK	0.115

© November 2026 - All Rights Reserved