

Thimble G-414, Crosby - Extra heavy

Product information

General:

The use of the G-414 extra heavy thimbles for your wire rope slings ensures a greater protection against wear of the wire rope and deformation of the wire rope eye.

Features:

- Longer service life.

Material: Steel

Marking: According to standard

Finish: Hot-dip galvanised

Standard: EN 13411-1



| Part code | Rope Ø range mm | Finish | A, | B, | C, | D, | E, | F, | G, | H, | Weight kg/100pc |
|--------------|-----------------|------------|------|------|------|------|------|------|------|------|-----------------|
| 123101000230 | 9-10 | Galvanized | 73,0 | 54,0 | 54 | 28.7 | 16,8 | 10.4 | 2.8 | 8.65 | 9.8 |
| 123101200230 | 11-12 | Galvanized | 82.5 | 60.5 | 60.5 | 31.8 | 18.8 | 11.9 | 3.3 | 9.65 | 15.7 |
| 123101500230 | 13-15 | Galvanized | 92,0 | 70,0 | 70,0 | 38.1 | 23.4 | 13,5 | 3.55 | 10.4 | 23.1 |
| 123101600230 | 16 | Galvanized | 108 | 82.5 | 79.5 | 44.5 | 26,2 | 16.8 | 4.05 | 12.7 | 34.3 |
| 123102000230 | 18-20 | Galvanized | 127 | 95.5 | 96,5 | 51 | 33,0 | 19.8 | 5.6 | 16.8 | 72 |
| 123102200230 | 22 | Galvanized | 140 | 108 | 108 | 57 | 37,3 | 23.9 | 5.6 | 19.1 | 81 |
| 123102600230 | 24-26 | Galvanized | 156 | 114 | 125 | 63.5 | 44,5 | 26.9 | 6.35 | 22.4 | 142 |
| 123103200230 | 28-32 | Galvanized | 178 | 130 | 149 | 73 | 47,8 | 33.3 | 6.35 | 28.7 | 181 |
| 123103500230 | 32-35 | Galvanized | 230 | 165 | 173 | 89 | 57,2 | 36.6 | 9.65 | 28.7 | 402 |
| 123103800230 | 35-38 | Galvanized | 229 | 159 | 181 | 89 | 66,5 | 39.6 | 12.7 | 28.7 | 587 |
| 123104000230 | 40 | Galvanized | 286 | 203 | 207 | 102 | 76,2 | 43.7 | 12.7 | 35.1 | 771 |
| 123104400230 | 44 | Galvanized | 310 | 229 | 216 | 114 | 77,7 | 46.7 | 12.7 | 33.3 | 805 |
| 123105200230 | 48-52 | Galvanized | 384 | 305 | 264 | 152 | 85,9 | 53,0 | 12.7 | 38.1 | 1,259 |
| 123105600230 | 56 | Galvanized | 435 | 356 | 302 | 178 | 98,6 | 60.5 | 16,0 | 41.4 | 1,792 |

Blueprint

