



## Alloy Swivel Hoist Hook - 8-175

### Product information

With brass washer / without ball bearing.

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Magnaflux crack detection is performed 100% on each batch.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, All parts with batch number for quality certified and traceability.

**Temperature range:** Tempering temperature minimum 400°C.

**Standard:** EN 1677-2

**Warning:** This hook is a positioning device and is not intended to rotate under load. When using hoist hook with grade 100 chain, YOKEhoist hooks is recommended to be grinded the WLL (which is for a safety factor 5:1) off the hook.

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	For chain Grade 10 Ø mm	A mm	B mm	C mm	D mm	G mm	H mm	K mm	L mm	P mm	P1 mm	T mm	Weight kg	Total price
På forespørsel	BB	1.4	6	32	23	25	12	80	21	126	158	24	19	18	0.7	N/A
På forespørsel	CC	2.5	7,8	36	29	26	13	91	25	143	181	24	20	22	0.9	N/A
På forespørsel	DD	4	10	41	35	29	16	102	29	172	217	28	25	24	1.5	N/A
På forespørsel	EE	6.7	13	46	44	38	21	130	36	211	269	35	31	31	3.2	N/A
På forespørsel	FF	10	16	61	51	49	23	166	46	258	328	43	39	42	5.7	N/A
På forespørsel	GG	16	20	74	82	62	25	196	58	326	409	61	57	48	9.5	N/A
På forespørsel	HH	19	22	97	96	65	33	221	64	372	471	72	62	56	16.5	N/A

## Blueprint

