

Master Link Grab 1 Assy X-A05

Product information



At least 25% greater WLL than traditional Grade 8 products.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Fully integrated shortening hooks and master link.
No reduction in WLL when shortening chain.
Speedy assembly.
Light weight system.
Cost effective compared to slings which use multiple components.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.


[... Read more](#)

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-4

Safety factor: 4:1
Grade: 10

Master Link Grab 1 Assy X-A05

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL mm	WLL 45- 60° ton	WLL 0-45° ton	Can be used to single hook acc	D mm	A mm	B mm	K mm	Weight kg
402100200470	6	2	196	1,4	2	4	13	120	70	196	0.9
402100350470	8	3.5	262	2,5	3,5	6	19	160	95	262	2.2
402100560470	10	5.6	295	4	5,6	10	22	170	105	295	3.8
402100940470	13	9.4	348	6,7	9,4	10	28	190	110	348	7
402101400470	16	14	432	10	14	12	32	230	130	432	13.6