Lifting Solutions Group
Axel Johnson International

Welded Master Link Assembly X-0082

Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

... *Read more*

Material: Quenched and Tempered Alloy Steel
Marking: According to standard, CE-mark, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-4

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Welded Master Link Assembly X-0082

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	EWL mm	Proof Load kN	For chain, 2-leg mm	Used to single hook acc. to DIN 15401 No.	D mm	A mm	B mm	d mm	a mm	b mm	Weight kg
402100560440	ED-28	7-8	5.6	374	137	10	25	28	340	180	16	70	34	5.4
402100950440	ED-32	10	9.5	425	233	13	25	32	340	180	19	85	40	7.4
402101410440	ED-40	13	14.1	455	343	16	25	40	340	180	22	115	50	12.1

© November 2026 - All Rights Reserved