

Chain KLB, Gunnebo Short Link lifting chain

Product information




Quality blue painted Chain KLB Short Link KL, Grade 80, quenched and tempered
... [Read more](#)

Marking: According to standard
Finish: Quenched and tempered.
Standard: EN 818-2

Safety factor: 4:1
Grade: 8

Chain KLB, Gunnebo Short Link lifting chain

Blueprint



Technical data

| Part code | Chain diameter mm | WLL ton | Min. breaking force kN | Length m | d mm | P mm | w1mm mm | Weight kg/m |
|-----------------|----------------------|------------|---------------------------|-------------|------|------|---------|----------------|
| 203100702000120 | 7 | 1.5 | 62 | 200 | 7 | 21 | 10 | 1.1 |
| 203100802000120 | 8 | 2 | 80.6 | 200 | 8 | 24 | 11 | 1.4 |
| 203101001000120 | 10 | 3.2 | 130 | 100 | 10 | 30 | 14 | 2.3 |
| 203101301000120 | 13 | 5.4 | 214 | 100 | 13 | 39 | 17.7 | 3.8 |
| 203101601000120 | 16 | 8.2 | 322 | 100 | 16 | 48 | 21.9 | 5.6 |
| 203102200500120 | 22 | 15.5 | 610 | 50 | 22 | 66 | 29.5 | 10.6 |
| 203102600500120 | 26 | 21.6 | 850 | 50 | 26 | 78 | 35 | 14.8 |
| 203103200500120 | 32 | 32.8 | 1,300 | 25 | 32 | 96 | 44.6 | 21.6 |