



## Lifting Eye RUD VWBG-V

### Product information

- Rotating 360°, pivoting 230°
- Optical markings for easy determination for withdraw from service
- Ball bearing

**Marking:** According to standard

**Standard:** EN 1677-1

**Safety factor:** 4:1

| Part Code   | WLL  | A mm | B mm | C mm | D mm | E mm | F mm | G mm | M mm | T mm | Weight | Delivery time |
|-------------|------|------|------|------|------|------|------|------|------|------|--------|---------------|
| 42157103720 | 0.3  | 8    | 31   | 29   | 30   | 27   | 13   | 36   | M8   | 76   | 0.18   | 3             |
| 42157103715 | 0.45 | 8    | 31   | 29   | 33.5 | 30   | 17   | 38   | M10  | 78   | 0.29   | 7             |
| 42157100180 | 0.6  | 10   | 49   | 35   | 42   | 36   | 21   | 47   | M12  | 107  | 0.44   | 7             |
| 42157100800 | 2    | 13   | 54   | 35   | 62   | 55   | 33   | 67   | M20  | 137  | 1.42   | 7             |
| 42157100640 | 3.5  | 18   | 66   | 40   | 81   | 70   | 40   | 88   | M24  | 173  | 2.63   | 7             |
| 42157100650 | 5    | 22   | 90   | 50   | 99   | 85   | 50   | 106  | M30  | 221  | 5.09   | 7             |

# Blueprint

