



Pad Eye S-264, Crosby

Product information

- Excellent welding qualities.
- Widely used on farm machinery, trucks, steel hulled marine vessels and material handling equipment.
- Reference American Welding Society specifications for proper welding procedures.

Material: Forged Steel — Quenched and Tempered.

Warning: Pad Eyes are designed to be attached to any structure, equipment, vehicles or machinery in which there is a need or desire for an eye, without the drilling and/or threading required for an eyebolt attachment. The normal method of attachment for pad eyes is by welding. Since Crosby cannot control the method of attachment (i.e. weld quality and size), a Working Load Limit is not provided for pad eyes.

| Part code | Size | B mm | C mm | D mm | E mm | G mm | H mm | L mm | Weight kg | Delivery time |
|--------------|------|------|------|------|------|------|------|------|-----------|---------------|
| 421100050950 | 1 | 9.65 | 6.35 | 22.4 | 10.4 | 22.4 | 3.3 | 26.2 | 0.03 | 3 |
| 421100050955 | 1.5 | 16 | 6.35 | 25.4 | 11.2 | 28.7 | 4.05 | 33.3 | 0.047 | 3 |
| 421100120950 | 2 | 19.1 | 9.65 | 26.9 | 12.7 | 38.1 | 4.85 | 41.4 | 0.096 | 7 |
| 421100240950 | 4 | 25.4 | 14.2 | 36.6 | 19.8 | 54 | 5.6 | 59.5 | 0.237 | 7 |
| 421100330950 | 5 | 31.8 | 17.5 | 44.5 | 20.6 | 67 | 6.35 | 70 | 0.374 | 7 |

Blueprint

