Lifting Solutions Group
Axel Johnson International

Carabiner Pulley ROLLCLIP Z, Petzl

Product information



ROLLCLIP Z is a pulley-carabiner with a gate opening on the non-pulley side to facilitate installation on anchors and devices.
It is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system.

- Easier handling:
  - Sheave mounted on sealed ball bearings for excellent efficiency
  - Gate opening on the non-pulley side, to facilitate installation on devices
  - Keylock system prevents any accidental snagging of the carabiner when putting the pulley in place
- H cross-section of carabiner:
  - Ensures an improved strength-to-weight ratio
  - Protects markings from abrasion
- Two locking systems available:
  - TRIACT-LOCK: automatic locking with triple-action gate opening
  - SCREW-LOCK: the manual screw-lock with red band provides a visual warning when the carabiner is unlocked
- Major axis strength: 20kN
- Minor axis strength: 8kN
- Open gate strength: 7kN

... *Read more*

Material: Aluminium
Marking: According to standard, CE-marked, UKCA-marked
Standard: EN 12278, EN 362

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Carabiner Pulley ROLLCLIP Z, Petzl

Technical data

Part code	Min. breaking force kN	Rope Ø mm	Locking device*	Gate Opening mm	Weight kg
823500000941	8	7-13	SCREW-LOCK	21	0.105
823500000940	8	7-13	TRIACT-LOCK	20	0.11

© November 2026 - All Rights Reserved