

## Dee Shackle BN Green Pin® Bolt G-4153

## **Product information**

The Green Pin<sup>®</sup> Dee Shackle BN is a dee shackle with a safety bolt. The shackle offers a double safety (split pin and safety bolt) which prevents accidental unscrewing of the pin. Its long-term durability is assured due to galvanization. Particularly important for use offshore, the shackle conforms to a wide range of certifications from class societies such as DNV GL. The Green Pin<sup>®</sup> Dee Shackle BN is suitable for one-leg lifting systems only and is available in a range with a working load limit from 2 up to 85 ton.

Certification on request: 2.1, 2.2, 3.1, MTCa, DNV 2.7-1a, DNV 2.7-1b, DNVGL-ST-0378, ABS PDA, ABS MA

Material: Bow and pin high tensile steel, guenched and tempered

Marking: According to standard, CE-marked Temperature range: -40°C up to +200°C

Finish: Hot dip galvanized Standard: EN 13889

Safety factor: 6:1 Grade: 6

Part code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	Weight kg
420103500560	35	50	57	111	50	83	171	305	269	26	17.35
420108500560	85	75	83	162	73	127	229	427	380	39	52.97

## Blueprint

