Lifting Solutions Group
Axel Johnson International

Pulley PRO TRAXION, Petzl

Product information

Very efficient loss-resistant progress capture pulley

The PRO TRAXION progress capture pulley was designed to allow rope installation while the pulley is connected to the anchor. With its large diameter sheave and great efficiency, it is particularly appropriate for hauling heavy loads on big walls. The side plate locks when loaded and prevents opening of the pulley during use.

- Min. rope diameter: 8 mm
- Max. rope diameter: 13 mm
- Sheave type: sealed ball bearings
- Sheave diameter: 38 mm
- Working load: 2 x 2,5 = 5 kN
- Breaking strength: 2 x 11 = 22 kN
- Working load as progress capture pulley: 2,5 kN
- Breaking strength as progress capture pulley: 4 kN
- Efficiency: 95 %

... *Read more*

Material: Aluminum, Stainless Steel, Nylon
Marking: According to standard, CE-mark, UKCA-marked
Standard: EN 567

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Pulley PRO TRAXION, Petzl

Technical data

Part code	Min. breaking force kN	Rope Ø mm	Weight kg
821500000410	22	8-13	0.265

© November 2026 - All Rights Reserved