



## Wire Rope Clip Crosby G-450

### Product information

Based on the catalog breaking strength of wire rope, Crosby wire rope clips have an efficiency rating of 80% for 3 mm through 22 mm sizes, and 90% for sizes 24 mm through 90 mm.

**Features:** Wire clips to secure and form a temporary termination on site.

**Material:** Steel

**Marking:** According to standard, ID code and Manufacturer's symbol

**Finish:** Galvanised

**Standard:** EN 13411-5

**Note:** All sizes except 68-72 mm and 85-90 mm meet the performance requirements of EN13411.

| Part Code    | Rope Ø range<br>mm | A<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | H<br>mm | Weight<br>kg/100pc | Delivery time |
|--------------|--------------------|---------|---------|---------|---------|---------|---------|---------|---------|--------------------|---------------|
| 121100700120 | 6-7                | 7.85    | 26.2    | 12.7    | 19.1    | 16.8    | 14.2    | 30.2    | 36.6    | 8.62               | 7             |
| 121100800120 | 8                  | 9.65    | 35.1    | 19.1    | 22.4    | 18.3    | 17.5    | 33.3    | 42.9    | 12.7               | 7             |
| 121101000120 | 9-10               | 11.2    | 38.1    | 19.1    | 25.4    | 23.1    | 19.1    | 41.4    | 49.3    | 21.8               | 7             |
| 121101300120 | 11-13              | 0.5     | 1.88    | 1       | 1.19    | 1.13    | 0.88    | 1.91    | 2.28    | 80                 | 7             |
| 121101500120 | 14-15              | 14.2    | 57      | 31.8    | 33.3    | 31      | 23.9    | 52.5    | 63.5    | 49.4               | 7             |
| 121102000120 | 18-20              | 15.7    | 70      | 36.6    | 38.1    | 35.8    | 26.9    | 57      | 72      | 64                 | 3             |
| 121102200120 | 22                 | 19.1    | 79      | 41.1    | 44.5    | 40.4    | 31.8    | 62      | 80.5    | 96                 | 3             |
| 121103000120 | 28-30              | 19.1    | 98.5    | 51      | 51      | 48.5    | 31.8    | 71.5    | 91      | 128                | 7             |
| 121103600120 | 36                 | 22.4    | 118     | 58.5    | 59.4    | 58.5    | 36.6    | 79.5    | 106     | 200                | 7             |
| 121104600120 | 44-46              | 28.7    | 146     | 70      | 77.5    | 74.5    | 46      | 97      | 134     | 424                | 3             |
| 121105200120 | 48-52              | 31.8    | 164     | 76      | 86      | 77      | 51      | 113     | 149     | 590                | 7             |
| 121106500120 | 62-65              | 31.8    | 195     | 87.5    | 105     | 93.5    | 51      | 119     | 168     | 862                | 7             |

# Blueprint

