

Rope AXIS 11 mm with sewn termination

Product information



Low stretch kernmantle rope with sewn termination for use with ASAP and ASAP LOCK mobile fall arresters.

The AXIS 11 mm low stretch kernmantle rope with sewn termination is designed for use with an ASAP or ASAP LOCK mobile fall arrester and an ASAP'SORBER or ASAP'SORBER AXESS energy absorber. It has a sewn termination with a protective sheath that helps keep the connector in position, meeting the requirements of the EN 12841 European standard for fall protection. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. The rope is available in six lengths.

- Strength with sewn termination: 22 kN
- Impact force (factor 0,3): 5,2 kN
- Number of factor 1 falls: 12
- Construction: 32 carrier
- Percentage of sheath: 41 %
- Static elongation: 3 %

... [Read more](#)

Material: Polyester, nylon

Marking: According to standard, CE-marked, UKCA-marked

Standard: EN 1891-A

Rope AXIS 11 mm with sewn termination

Technical data

Part code	Diameter mm	Min. breaking force kN	Length m	Colour	Weight kg/m
823101000140	11	22	10	White	0.082
823102000141	11	22	20	White	0.082
823103000142	11	22	30	White	0.082
823104000140	11	22	40	White	0.082
823105000140	11	22	50	White	0.082
823106000140	11	22	60	White	0.82