



## Rope AXIS 11 mm with sewn termination

### Product information

Low stretch kernmantle rope with sewn termination for use with ASAP and ASAP LOCK mobile fall arresters.

The AXIS 11 mm low stretch kernmantle rope with sewn termination is designed for use with an ASAP or ASAP LOCK mobile fall arrester and an ASAP'SORBER or ASAP'SORBER AXESS energy absorber. It has a sewn termination with a protective sheath that helps keep the connector in position, meeting the requirements of the EN 12841 European standard for fall protection. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. The rope is available in six lengths.

- Strength with sewn termination: 22 kN
- Impact force (factor 0,3): 5,2 kN
- Number of factor 1 falls: 12
- Construction: 32 carrier
- Percentage of sheath: 41 %
- Static elongation: 3 %

**Material:** Polyester, nylon

**Marking:** According to standard, CE-marked, UKCA-marked

**Standard:** EN 1891-A

| Part code    | Diameter<br>mm | Min. breaking force<br>kN | Length<br>m | Colour | Weight<br>kg/m |
|--------------|----------------|---------------------------|-------------|--------|----------------|
| 823102000141 | 11             | 22                        | 20          | White  | 0.082          |
| 823103000142 | 11             | 22                        | 30          | White  | 0.082          |
| 823104000140 | 11             | 22                        | 40          | White  | 0.082          |