

## Polypropylene Fibre Rope 3-Strand.



### Product information

Fibre rope of polypropylene for all different kinds of applications like: tarpaulin- and towing-ropes, lifting slings, ropes for the fishing industry, cargo nets, rope ladders, and more. The structure of the fibre rope makes it non-sliding in knots and splices.

**Design:** Spliced fibre.

**Specific gravity:** 0,91 (floats).

**Melting point:** Approx. 165°C.

**Elongation at MBL:** Approx. 30%.

**Strength wet/dry:** 100%

**Shock Absorption:** Very Good

**Water Absorption:** None

**Abrasion Resistance:** Good

**Material:** Polypropylene, resistant to rot, most acids and alkalis. The fibre is UV-stabilized against sunlight.

**Marking:** According to standard

**Finish:** Blue.

**Standard:** EN ISO 1346

Part Code	Diameter mm	Length m	Delivery time
300300400500010	4	50	7
300300600500010	6	50	3
300300601100010	6	110	3
300300606000010	6	600	3
300300800500010	8	50	3

300300801100010	8	110	3
300300803500010	8	350	3
300301000500010	10	50	3
300301001100010	10	110	3
300301002200010	10	220	7
300301200500010	12	50	7
300301201100010	12	110	3
300301201500010	12	150	3
300301400500010	14	50	3
300301401100010	14	110	3
300301600500010	16	50	3
300301600900010	16	90	3
300301601100010	16	110	3
300301801100010	18	110	3
300302001100010	20	110	3
300302201100010	22	110	3
300302401100010	24	110	3
300302801100010	28	110	3