Lifting Solutions Group
Axel Johnson International

SRL Nano-Lok G2, 3M Mini Block Single Leg

Product information



The next generation 3M Dbi-Sala Nano-lok G2 personal Self Retracting Lifeline: light on weight and heavy on features.

Features:

- Improved safety:
  - User weight up to 140 kgs, also with anchor point at foot level.
  - More scaffold hooks available, also gate rated.
- Longer lasting: better housing and nitrile rubber shock absorber.
- Faster installing upon harness with new steel SRL fast connection system connector.
- Dorsal D-ring stays free for rescue with fast connection system.
- Easier inspection.
- Light weight.
- Fall impact indicator.
- Swivel in connector helps to prevent twisting of the webbing.
- Easy changing from single to twin leg application – and reverse with SRL fast connector.
- Available with several connectors on housing side (**connection A**) and connectors on lanyard end (**connection B**)

... *Read more*

Material: Housing: Nylon - Web: Dyneema® and polyester - Absorber Cover: Nitrile rubber - Top Ring: Zinc plated steel
Marking: According to standard
Temperature range: -40°C up to 60°C
Standard: EN 360
Warning: These models are not specifically tested for sharp edge falls. For these situations see the Nanolok Edge blocks.

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

SRL Nano-Lok G2, 3M Mini Block Single Leg

Technical data

Part code	Code	Length m	connection A	connection B	Weight kg
822100200410	3101207	2	SRL fast connector 3100197	Alu. hook 57mm opening 2007153	1.31
822100210410	3101709	2.1	Alu carabiner 19mm opening 200025	Alu. hook 63.5 mm opening 2000214	1.59

© November 2026 - All Rights Reserved