

## **Starcon Ring Clutch**

## **Product information**

The Starcon ring clutch is a specially designed component with a bolt-shaped ring that grips the hole of the Starcon STA anchor. It enables quick and secure mounting of the ring coupling to the STA anchors by means of a locking bolt that mechanically locks to the anchor.

The ring coupling can be easily connected to a sling or hook, making lifting both fast and safe. It is ideal for use with lifting equipment and cranes, ensuring efficient and reliable handling of concrete elements.

Areas of application: The Starcon ring clutch is used for lifting Starcon STA anchors

Advantages: Ensures handling of concrete elements.

Enables safe lifting in all directions.

Quick and easy installation.

Load group: 2.5t – 10t

Technical information: CE marking according to MD 2006/42 EF

Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, batch code, load group + S(Starcon)
Finish: Electro-galvanized - Corrosion class C3 - ISO 12944-2.

Part code	Load grp. t	Packing Qty.	a mm	b mm	c mm	d mm	t mm	L mm	Weight kg
650290025001	2.5	10	70	54	79	27	12.5	223	0.95
650290050001	5	4	85	59.5	107	37	17	281	1.5
650290100001	10	1	110	82.5	148	50	25	352	3.18

## Blueprint

