Lifting Solutions Group
Axel Johnson International

Master Link Grade 8

Product information



For 1-and 2 leg slings.

... *Read more*

Material: Quenched and tempered alloy steel grade 8.
Marking: According to standard, Code and grade.
Finish: Painted.
Standard: EN 1677-4
Warning: Not to be heat treated.


Safety factor: 5:1
Grade: 8

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Master Link Grade 8

Blueprint



Technical data

Part code	Code	WLL ton	Dim./Type	D mm	B mm	L mm	Weight kg
401100270080	13.B.6*	2.7	13.B.6*	13	60	115	0.4
401100410080	16.B.6*	4.1	16.B.6*	16	70	120	0.6
401100670080	20.B.6*	6.7	20.B.6*	20	82	150	1.1
401100820080	22.B.6*	8.2	22.B.6*	22	90	170	1.6
401101070080	25.B.6*	10.7	25.B.6*	25	103	190	2.3
401101290080	28.B.6*	12.9	28.B.6*	28	113.5	209	3.2
401101710080	32.B.6*	17.1	32.B.6*	32	140	270	5.3
401101910080	38.B.7	19.1	38.B.7	38	220	420	11
401102760080	45.B.7	27.6	45.B.7	45	250	470	16.5
401102810080	38.B.6	28.1	38.B.6	38	140	270	7.5
401103830080	45.B.6	38.3	45.B.6	45	170	320	12.5
401104500080	50.B.6	45	50.B.6	50	200	380	18
401106530080	60.B.6	65.3	60.B.6	60	220	430	30
401108440080	70.B.6	84.4	70.B.6	70	250	475	44

© November 2026 - All Rights Reserved