



Master Link Assembly

Product information

For 3-and 4 leg slings.

Material: Quenched and tempered alloy steel grade 8.

Marking: Code and grade.

Finish: Painted.

Warning: Not to be heat treated.

Safety factor: 5:1

Grade: 8

Part code	WLL ton	Dim./Type	Intermediate M.L Type	Intermediate M.L Dim.	Masterlink	Dimensions mm	Weight kg
401100410090	4.1	Q.16.B	13.B.5	51x95	16.B.6	70x120	1.2
401100650090	6.5	Q.20.B	16.B.6	70x120	20.B.7	90x170	2.5
401100820090	8.2	Q.22.B	20.B.6	80x150	22.B.8	90x170	3.8
401101070090	10.7	Q.25.B	20.B.6	80x150	25.B.6	100x190	4.5
401101290090	12.9	Q.28.B	22.B.6	90x170	28.B.6	113.5x209	6.4
401101710090	17.1	Q.32.B	25.B.6	100x190	32.B.6	140x270	9.9
401102810090	28.1	Q.38.B	32.B.6	140X270	38.B.6	140x270	18.2
401103830090	38.3	Q.45.B	38.B.6	140x270	45.B.6	170x320	27.7
401104500090	45	Q.50.B	38.B.6	200x380	50.B.6	200x380	33.2
401106530090	65.3	Q.60.B	50.B.6	200x380	60.B.6	220x430	66
401108400090	84	Q.70.B	60.B.6	220x430	70.B.6	250x500	103