

Eye Self Locking Hook 8-025, Yoke

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured..
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Powder coating


Standard: EN 1677-3

Safety factor: 4:1

Grade: 8

Eye Self Locking Hook 8-025, Yoke

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	D mm	H, mm	K mm	Pmm mm	T mm	Weight kg
401300110910	6	1.12	21	10	19	110	29	15	0.5
401300200910	7-8	2	25	11	24	136	34	20	0.8
401300320910	10	3.15	32	13	30	167	44	26	1.4
401300530910	13	5.3	40	16	39	207	52	30	2.9
401300800910	16	8	52	21	49	252	60	36	5.7
401301250910	18-20	12.5	64	23	62	282	90	48	8.5
401301500910	22	15	70	24	63	319	80	49	12.5
401302120910	26	21.2	80	25	69	343	99	56	14.5
401302500910	28	25	90	28	81	401	120	63	24.9