



Eye Self Locking Hook 8-025, Yoke

Product information

- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured..
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflex crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Powder coating

Standard: EN 1677-3

Safety factor: 4:1

Grade: 8

Part Code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
401300110910	6	1.12	21	10	19	110	29	15	0.5	3
401300200910	7-8	2	25	11	24	136	34	20	0.8	3
401300320910	10	3.15	32	13	30	167	44	26	1.4	3
401300530910	13	5.3	40	16	39	207	52	30	2.9	3
401300800910	16	8	52	21	49	252	60	36	5.7	3
401301250910	18-20	12.5	64	23	62	282	90	48	8.5	3
401301500910	22	15	70	24	63	319	80	49	12.5	3
401302120910	26	21.2	80	25	69	343	99	56	14.5	3
401302500910	28	25	90	28	81	401	120	63	24.9	7

Blueprint

