



Clevis Sling Hook 8-043/S, Yoke

Product information

- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel.

Temperature range: -40°C up to +200°C

Finish: Powder coating

Safety factor: 4:1

Grade: 8

| Part Code | Chain diameter mm | WLL ton | A mm | H mm | K mm | P1 mm | T mm | Weight kg | Delivery time |
|--------------|----------------------|------------|---------|---------|---------|----------|---------|--------------|---------------|
| 401300200890 | 7-8 | 2 | 9 | 22 | 98 | 27 | 18 | 0.6 | 3 |
| 401300320890 | 10 | 3.15 | 11 | 29 | 121 | 34 | 23 | 1.2 | 3 |
| 401300530890 | 13 | 5.3 | 14 | 37 | 147 | 44 | 30 | 2.3 | 3 |
| 401300800890 | 16 | 8 | 18 | 42 | 166 | 48 | 39 | 3.7 | 3 |
| 401301250890 | 18-20 | 12.5 | 21 | 50 | 200 | 56 | 47 | 6.5 | 3 |

Blueprint

