



## Clevis Sling Hook 8-043/S, Yoke

### Product information

- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

**Material:** Quenched and Tempered Alloy Steel.

**Temperature range:** -40°C up to +200°C

**Finish:** Powder coating

**Safety factor:** 4:1

**Grade:** 8

| Part code    | Chain diameter<br>mm | WLL<br>ton | A mm | H<br>mm | K<br>mm | P1<br>mm | T<br>mm | Weight<br>kg |
|--------------|----------------------|------------|------|---------|---------|----------|---------|--------------|
| 401300200890 | 7-8                  | 2          | 9    | 22      | 98      | 27       | 18      | 0.6          |
| 401300320890 | 10                   | 3.15       | 11   | 29      | 121     | 34       | 23      | 1.2          |
| 401300530890 | 13                   | 5.3        | 14   | 37      | 147     | 44       | 30      | 2.3          |
| 401300800890 | 16                   | 8          | 18   | 42      | 166     | 48       | 39      | 3.7          |
| 401301250890 | 18-20                | 12.5       | 21   | 50      | 200     | 56       | 47      | 6.5          |

## Blueprint

