Lifting Solutions Group
Axel Johnson International

Polyethylene Rope, 3-Strand

Product information



Rope made of polyeten for applications like mooring, commercial fishing and industrial needs.

Design: 3 strand.

Specific gravity: 0.93(floats).
Melting point: Apx. 130 °C.
Elongation: Apx. 18%.

... *Read more*

Material: Polyeten. It is a smooth rope, resistant to rot and it has a relatively high elongation.
Finish: Orange.

© October 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Polyethylene Rope, 3-Strand

Technical data

Part code	Diameter mm	Min. breaking force kN	MBL ton	Rope ends	Weight kg/110m
300300600000040	6	3.9	0.4	Plain ends	3.6
300300800000040	8	6.8	0.7	Plain ends	5.2
300301000000040	10	10.7	1.1	Plain ends	5.4
300301200000040	12	15.6	1.6	Plain ends	7.9
300301400000040	14	20.6	2.1	Plain ends	10.5
300301600000040	16	27.4	2.8	Plain ends	14.1
300301800000040	18	34.3	3.5	Plain ends	17.7
300302000000040	20	42.1	4.3	Plain ends	22
300302200000040	22	50	5.1	Plain ends	26.7
300302400000040	24	59.8	6.1	Plain ends	32.5
300302800000040	28	80.4	8.2	Plain ends	43.2

© October 2026 - All Rights Reserved