



## Polyethylene Rope, 3-Strand

### Product information

Rope made of polyeten for applications like mooring, commercial fishing and industrial needs.

**Design:** 3 strand.

**Specific gravity:** 0.93(floats).

**Melting point:** Apx. 130 °C.

**Elongation:** Apx. 18%.

**Material:** Polyeten. It is a smooth rope, resistant to rot and it has a relatively high elongation.

**Finish:** Orange.

Part Code	Diameter mm	Min. Breaking force kN.	MBL	Rope ends	Weight kg/110m	Delivery time
300300600000040	6	3.9	0.4	Plain ends	3.6	3
300300800000040	8	6.8	0.7	Plain ends	5.2	3
300301000000040	10	10.7	1.1	Plain ends	5.4	3
300301200000040	12	15.6	1.6	Plain ends	7.9	3
300301400000040	14	20.6	2.1	Plain ends	10.5	3
300301600000040	16	27.4	2.8	Plain ends	14.1	3
300301800000040	18	34.3	3.5	Plain ends	17.7	3
300302000000040	20	42.1	4.3	Plain ends	22	3
300302200000040	22	50	5.1	Plain ends	26.7	7
300302400000040	24	59.8	6.1	Plain ends	32.5	3
300302800000040	28	80.4	8.2	Plain ends	43.2	3