Lifting Solutions Group
Axel Johnson International

Polyester Rope, 3-Strand

Product information



General: Polyester rope for typical applications like mooring lines, tie up lines, deck and anchor lines, use in rigging etc.

Specific gravity: 1,38 (sinks).
Melting point: 265°C.
Elongation: 15%.

... *Read more*

Material: Polyester fibre. It's a smooth and flexible rope, with high strength with excellent resistant to outer and internal wearing. It has a low working elongation and has an excellent UV resista
Finish: Black.

© October 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Polyester Rope, 3-Strand

Technical data

Part code	Diameter mm	Min. breaking force kN	MBL ton	Length m	Colour	Weight kg/110m
300300803000070	8	10	1	300	Black	5.28
300301002000070	10	15.6	1.6	200	Black	8.36
300301201500070	12	22.5	2.3	150	Black	12.1
300301401300070	14	31.3	3.2	130	Black	16.3
300301600800070	16	40.2	4.1	80	Black	21.5
300301801100070	18	50	5.1	110	Black	27
300302001100070	20	61.8	6.3	110	Black	33.3
300302201100070	22	74.5	7.6	110	Black	40.4

© October 2026 - All Rights Reserved