

## Swivel Hoist Ring Crosby, HR 1000

---

### Product information



Swivel hoist ring HR-1000 from Crosby

- Forged bail provides the following:
  - Easily readable raised lettering showing the name Crosby or "CG" and PIC for material traceability.
  - Greater durability providing the increased "Toughness" desired in potentially abusive field conditions.
  - Larger opening than standard hoist ring bail.
- Top washer is color-coded for easy identification (Red for UNC threads and Silver for Metric threads)
- The Working Load Limit and recommended torque value are permanently stamped into each washer.
- Individually Proof Tested to 2-1/2 times Working Load Limit.
- UNC bolt specification is an alloy socket head cap screw to ASTM A 574. Metric bolt specification is a Grade 12.9 alloy socket head cap screw to DIN 912.
- BOLT SIZE IDENTIFICATION: The size of the bolt will be stated as in the drawing. Illustration shows meaning of each dimension given.


... [Read more](#)

---

**Safety factor:** 4:1

## Swivel Hoist Ring Crosby, HR 1000

### Blueprint



### Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G, mm	H, mm	Weight kg
42151068316	0.55	M10 X 1.5 X 40	15.2	93.7	24.6	15.7	11.2	57.7	35.1	0.3
42151068325	1.3	M12 x 1.75 x 55	15.5	162	49.8	31.8	19.1	107	63.5	1.5
42151068343	2.7	M20 x 2.50 x 70	30.5	162	49.8	31.8	19.1	107	63.5	1.6
42151068361	5.25	M24 x 3.00 x 90	35.4	220	75.2	41.4	25.4	159	82.6	4.8
42151068370	8.75	M30 x 3.50 x 140	66.2	285	94.2	50.8	31.8	199	102	9.7