



Swivel Hoist Ring Crosby, HR 1000

Product information

Swivel hoist ring HR-1000 from Crosby

- Forged bail provides the following:
 - Easily readable raised lettering showing the name Crosby or "CG" and PIC for material traceability.
 - Greater durability providing the increased "Toughness" desired in potentially abusive field conditions.
 - Larger opening than standard hoist ring bail.
- Top washer is color-coded for easy identification (Red for UNC threads and Silver for Metric threads)
- The Working Load Limit and recommended torque value are permanently stamped into each washer.
- Individually Proof Tested to 2-1/2 times Working Load Limit.
- UNC bolt specification is an alloy socket head cap screw to ASTM A 574. Metric bolt specification is a Grade 12.9 alloy socket head cap screw to DIN 912.
- BOLT SIZE IDENTIFICATION: The size of the bolt will be stated as in the drawing. Illustration shows meaning of each dimension given.

Safety factor: 4:1

| Part code | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | Weight kg | Delivery time |
|-------------|---------|------------------|------|------|------|------|------|------|------|-----------|---------------|
| 42151068316 | 0.55 | M10 X 1.5 X 40 | 15.2 | 93.7 | 24.6 | 15.7 | 11.2 | 57.7 | 35.1 | 0.3 | 7 |
| 42151068325 | 1.3 | M12 x 1.75 x 55 | 15.5 | 162 | 49.8 | 31.8 | 19.1 | 107 | 63.5 | 1.5 | 7 |
| 42151068343 | 2.7 | M20 x 2.50 x 70 | 30.5 | 162 | 49.8 | 31.8 | 19.1 | 107 | 63.5 | 1.6 | 7 |
| 42151068361 | 5.25 | M24 x 3.00 x 90 | 35.4 | 220 | 75.2 | 41.4 | 25.4 | 159 | 82.6 | 4.8 | 7 |
| 42151068370 | 8.75 | M30 x 3.50 x 140 | 66.2 | 285 | 94.2 | 50.8 | 31.8 | 199 | 102 | 9.7 | 7 |

Blueprint

