

## Lifting Eye RUD ACP-TURNADO



### Product information



- unique RUD spring mechanism
- No stopping of the lifting bale
- No dangerous transverse loads - no worst case
- Integrated RFID transponder to make checks easier
- Wear lenses for checking discard criteria

According to the EC-Machinery Directive 2006/42/EC

**Marking:** According to standard

**Temperature range:** -40°C up to +100°C.

**Standard:** EN 1677-1, EN ISO 12100

**Safety factor:** 4:1

| Part Code   | WLL ton | A mm  | B mm | C mm | D mm | E mm | F mm | G mm | H mm | I mm | K mm | L mm | M mm | N mm | T mm | Weight kg | Delivery time |
|-------------|---------|-------|------|------|------|------|------|------|------|------|------|------|------|------|------|-----------|---------------|
| 42157912061 | 0.7     | -     | 11   | 10.5 | 38   | 30   | 12   | 28   | 45   | 13   | 58   | 40   | M8   | 5    | 83   | 0.36      | 7             |
| 42157911052 | 12.5    | 106   | 32   | 32   | 82   | 70   | 45   | 60   | 128  | 55   | 168  | 105  | M36  | 22   | 189  | 7.1       | 7             |
| 42157911053 | 16      | 106   | 32   | 32   | 82   | 70   | 53   | 60   | 136  | 65   | 168  | 113  | M42  | 24   | 189  | 7.5       | 7             |
| 42157912630 | 20      | 127   | 45   | 45   | 103  | 90   | 61   | 78.5 | 169  | 75   | 204  | 139  | M48  | 24   | 235  | 16.04     | 7             |
| 42157912631 | 24      | 123.5 | 45   | 45   | 103  | 95   | 65   | 108  | 173  | 75   | 204  | 145  | M52  | 24   | 232  | 16.34     | 7             |
| 42157912632 | 27      | 123.5 | 45   | 45   | 103  | 95   | 70   | 108  | 178  | 75   | 204  | 150  | M56  | 24   | 232  | 16.5      | 7             |
| 42157912633 | 32.5    | 123.5 | 45   | 45   | 103  | 95   | 80   | 108  | 188  | 75   | 204  | -    | M64  | 24   | 232  | 17.19     | 7             |

## Blueprint

