

## Aluminium Gantry Crane PADC

---

### Product information



There are many sites which have the particularity of requiring mobile and in great quantities lifting equipments. Lightness and robustness are the advantages of aluminium gantry structure.

- Light construction
- Capacities
  - 250 kg
  - 500 kg
  - 1000 kg (span max. 6m)
  - 1600 kg (span max. 5m)
  - 2000 kg (span max. 4m)
- Bolted joints
- Easy assembly with 8 bolts between leg and beam
- Assembly requires 1 to 3 people, according to model
- Flexibility of movement due to its light weight
- Hollow-section gantry girder
- Hoist trolley provided
- Height under beam can be adjusted by single person
- Dismountable in 3 elements, with foldable feet
- Feet fold up for transport
- White polyamide wheels, with 2 locking wheels
- Maximum hoisting speed = 8m/min

#### Options

- Banded polyurethane wheels

... [Read more](#)

## Aluminium Gantry Crane PADC

Capacity (kg)	Span(m)	Working span (mm)	Adjustable height under beam
250	2	900	H0 = 1550 à 2150 H1 = 2150 à 3200 H2 = 3000 à 4000
	2,5	1400	
	3	1900	
	3,5	2400	
	4	2900	
	4,5	3400	
	5	3900	
	5,5	4400	
500	2	900	H0 = 1550 à 2150 H1 = 2150 à 3200 H2 = 3000 à 4000
	2,5	1400	
	3	1900	
	3,5	2400	
	4	2900	
	4,5	3400	
	5	3900	
	5,5	4400	
1000	2	900	H0 = 1550 à 2150 H1 = 2150 à 3200 H2 = 3000 à 4000
	2,5	1400	
	3	1900	
	3,5	2400	
	4	2900	
	4,5	3400	
	5	3900	
	5,5	4400	
1600	2	900	H0 = 1550 à 2150 H1 = 2150 à 3200 H2 = 3000 à 4000
	2,5	1400	
	3	1900	
	3,5	2400	
	4	2900	
	4,5	3400	
	5	3900	
2000	2	900	H0 = 1550 à 2150 H1 = 2150 à 3200 H2 = 3000 à 4000
	2,5	1400	
	3	1900	
	3,5	2400	
	4	2900	