Lifting Solutions Group
Axel Johnson International

Vertical Lifting Clamp IPU10J

Product information



The Crosby IPU10J vertical lifting clamp is designed for lifting, turning and transferring steel plates, sheets and fabricated components with larger thicknesses. Its enlarged jaw opening accommodates thicker materials, while the hinged hoisting eye allows lifting from different directions without side-loading the clamp. The clamp supports 180° load rotation between horizontal and vertical positions.

Best used for:

- Handling thick steel plates and fabricated components in industrial lifting operations.
- Vertical lifting, positioning and 180° turning of plates in workshops and fabrication facilities.

Product benefits:

- Enlarged jaw opening accommodates plate thicknesses from 40 to 155 mm, depending on capacity.
- Hinged hoisting eye enables multidirectional lifting without side-loading the clamp.
- Lock-open and lock-closed mechanism supports controlled attachment and release.
- Welded alloy steel body provides strength with compact dimensions.
- Individually proof tested to twice the WLL, with certification for documented verification.

... *Read more*


Material: Alloy Steel
Marking: According to standard, CE-mark, WLL, Logo, Type, Jaw opening, Serial number, Proof load test date
Temperature range: -40°C (-40°F) up to +100°C (+212°F)
Standard: EN 13155
Note: Min. load is 10% of WLL.

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Vertical Lifting Clamp IPU10J

Blueprint



Technical data

Part code	Code	WLL ton	Jaw width mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	K mm	J mm	Weight kg
502100450801650	4.5-IPU10J	4.5	40-80	126	302	515	80	336	84	95	20	44	18.9
502100601001650	6-IPU10J	6	50-100	115	270	432	75	281	82	72	20	-	26.5

© November 2026 - All Rights Reserved