Lifting Solutions Group
Axel Johnson International

Wire Rope Dyform Bristar 6

Product information

zZ G



Dyform Bristar 6 is a high performance compacted single layer constructed rope which incorporates an engineered extruded plastic profle between the 6 outer strands and the rope core for various cranes and industrial applications.

- Outstanding bending fatigue performance
- Improved support of outer strands in service

... *Read more*

Rope construction: Dyform Bristar 6x47 IWRC
Temperature range: -20°C up to 65°C

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Wire Rope Dyform Bristar 6

Technical data

Part code	Rope diameter mm	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Steel area mm²	Lubrication	Weight kg/100m
103105086250719	50.8	1,770	Galvanized	zZ	1,941.72	2,022.4	SupplierStandard	1,196
103106356250719	63.5	1,770	Galvanized	zZ	3,108.77	-	SupplierStandard	1,802
103106706270719	67	1,960	Galvanized	zZ	3,530.39	2,310	SupplierStandard	2,000
103107306240719	73	1,670	Galvanized	zZ	4,035.42	-	SupplierStandard	2,399

© November 2026 - All Rights Reserved