



Kiswire Neptune Hyrope BV 40 x K7

Product information

sZ zZ G

- Rotation poor
- Anointed
- High breaking strength
- Compact
- Large contact surface

Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
109805806270269	58	1,960	Galvanized	zZ	3,180	1,820	SupplierStandard	1,680
109807204270269	72	1,960	Galvanized	sZ	4,950	2,640	SupplierStandard	2,580
109807604270269	76	1,960	Galvanized	sZ	5,060	3,110	SupplierStandard	2,900
109807706270269	77	1,960	Galvanized	zZ	5,010	3,200	SupplierStandard	2,990
109808604270269	86	1,960	Galvanized	sZ	6,410	3,395	SupplierStandard	3,670
109808804270269	88	1,960	Galvanized	sZ	6,410	4,180	SupplierStandard	3,870
109809004270269	90	1,960	Galvanized	sZ	7,130	4,470	SupplierStandard	3,950
109809604270269	96	1,960	Galvanized	sZ	7,850	4,975	SupplierStandard	4,520
109809604300269	96	2,160	Galvanized	sZ	7,810	4,975	SupplierStandard	4,550
109810004270269	100	1,960	Galvanized	sZ	8,397	5,390	SupplierStandard	4,900