



## Metric Swivel Hoist Rings Crosby HR-125M

### Product information

#### Features:

- The Working Load Limit and Recommended Torque value are permanently stamped into each washer.
- Washer is color coded for easy identification: Silver - Metric thread.
- Bolt specification is a Grade 12.9 Alloy socket head cap screw to DIN 912.
- Designed to be used with ferrous workpiece only.
- BOLT SIZE IDENTIFICATION: The size of the bolt will be stated as in the blueprint. Illustration shows meaning of each dimension given.

**Safety factor:** 5:1

Part code	Torque Nm	WLL ton 4:1	WLL ton 5:1	A mm	B mm	C mm	D mm	E mm	ØF mm	G mm	H mm	Weight kg
42151016602	10	0.5	0.4	M8x1,25x40	16.9	69.9	24.6	11.8	8.5	47.5	29.9	0.17
42151016613	16	0.55	0.45	M10x1,50x40	16.9	69.9	24.6	11.8	8.5	47.5	28.1	0.18
42151016624	38	1.3	1.05	M12x1,75x50	16.9	123	49.8	22.3	17.5	85.1	60.4	1.05
42151016635	81	2.4	1.9	M16x2,00x60	26.9	123	49.8	22.3	17.5	85.1	56.3	1.11
42151016644	136	2.7	2.15	M20x2,50x65	31.9	123	49.8	22.3	17.5	85.1	52.3	1.17
42151016657	136	3.75	3	M20x2,50x75	27.8	167	75.2	34.7	25.4	124	76.6	3.09
42151016668	312	5.25	4.2	M24x3,00x80	32.8	167	75.2	34.7	25.4	124	70.5	3.21
42151016679	637	8.75	7	M30x3,50x120	61.7	222	94.2	44.5	30.5	157	102	6.53
42151016690	1,005	13.75	11	M36x4,00x150	54	318	120	60.7	44.5	215	142	16.8
42151016701	1,005	15.6	12.5	M42x4,50x160	64	318	120	60.7	44.5	215	136	17.4
42151016712	1,350	16.9	13.5	M48x5,00x160	74	318	120	60.7	44.5	215	130	18

# Blueprint

