



## Eye Bolt Shoulder Type Machinery Crosby M-279

### Product information

- Working load limits shown are for in-line pull.
- Recommended for in-line pull.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.

**Material:** Forged steel - quenched and tempered.

**Safety factor:** 4:1

Part Code	WLL ton	Thread mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg	Delivery time
421100020690	0.2	M6 x 1.0	M6 x 1.0	13	28.7	19.1	47	4.9	13.5	19.6	0.03	7
421100040690	0.4	M8 x 1.25	M8 x 1.25	13	35.1	22.4	54.6	6.4	15	24.1	0.05	7
421100060690	0.64	M10 x 1.5	M10 x 1.5	17	41.1	25.4	64.3	7.9	17.5	26.5	0.07	7
421100100690	1	M12 x 1.75	M12 x 1.75	20.5	49.5	30.2	77.7	9.7	23.1	32.8	0.11	7
421100180690	1.8	M16 x 2.0	M16 x 2.0	27	60.5	35.1	96	12.7	28.7	38.9	0.25	7
421100250690	2.5	M20 x 2.5	M20 x 2.5	30	70	38.1	108	16	35.1	43.4	0.42	7
421100400690	4	M24 x 3.0	M24 x 3.0	36	95.5	51	142	22.4	46	58.4	1.05	7
421100500690	5	M27 x 3.0	M27 x 3.0	69.8	107	57.1	183	24.6	52.3	59.7	1.42	7
421100600690	6	M30 x 3.5	M30 x 3.5	45	114	63.5	171	25.4	58	69.3	1.77	7
421100850690	8.5	M36 x 4.0	M36 x 4.0	54	140	76	207	31.8	70	83.3	3.12	7
421101400690	14	M42 x 4.5	M42 x 4.5	95.2	159	88.9	266	35	76.2	91.4	4.58	7

# Blueprint

