Lifting Solutions Group
Axel Johnson International

Fire Extinguisher CGS FE9CR-B

Product information



Area of use
The CGS foam fire extinguisher AB class is suitable for use against A, B fires. Test valve for easy pressure testing. Internally treated with European quality coating. The extinguisher can also be used for fires in electrical systems up to 1000V.

The fire extinguisher is PFAS free.

Function of the agent
The foam suffocates the fire by preventing the supply of oxygen. Additionally, the foam alters the surface tension of the extinguishing water, making it easier to penetrate the burning material. The foam will form a layer over the fire site, preventing the fire gases from penetrating.

Typical areas of use include: Industrial settings, public facilities, workshops, petrochemical industry, agriculture, maritime, residential areas, offices, shops, schools, etc.

In compliance with EN3-7 and Wheelmark.

... *Read more*

Material: Cylinder: Steel, Propellant: Nitrogen
Marking: CE-mark
Temperature range: 0°C up to +60°C
Note: The fire extinguisher must always be recharged after use, even if only parts of the contents have been used. Recharging requires special equipment. Contact an authorized service workshop. Use only specified extinguishing agents and spare parts.

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fire Extinguisher CGS FE9CR-B

Technical data

Part code	Width mm	Model	Height mm	Working pressure (bar)	Weight kg
8905600196	185	FE9CR-B	5,750	12	14.1

© November 2026 - All Rights Reserved