Lifting Solutions Group
Axel Johnson International

Eye Swivel Hook 8-049N

Product information

- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, CE-marked
Temperature range: Tempering temperature minimum 400°C
Standard: EN 1677-2

Safety factor: 4:1
Grade: 8

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Eye Swivel Hook 8-049N

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg
420500200850	YSWN	7-8	2	36	27	12	22	155	26	18	0.9
420500320850	YSWN	10	3.15	41	37	26	29	189	36	23	1.6
420500530850	YSWN	13	5.3	46	40	21	35	233	42	28	3.4
420500800850	YSWN	16	8	60	50	22	44	280	50	35	5.1
420501250850	YSWN	18-20	12.5	74	82	25	65	356	56	49	9.5

© October 2026 - All Rights Reserved