



Horizontal Lifting Clamp FHX/FHSX

Product information

For horizontal lifting and transporting of steel plates and other non-deflecting materials. Jaw openings available from: 0 to 150 mm. Only to be used and only sold in pairs.

Model FHX: Standard clamp

Model FHSX: Clamp with enlarged jaw opening.

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

Temperature range: - 40°C up to +100°C

Standard: EN 13155

Note: Must always be used in pairs (or multiple pairs)

Warning: Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm²)

| Part code | Code | WLL ton | Jaw width mm | V mm | S mm | W mm | T mm | H mm | X mm | U mm | Y mm | Weight kg |
|-----------------|--------|---------|--------------|------|------|------|------|------|------|------|------|-----------|
| 502100100350670 | 1 FHX | 1 | 0-35 | 140 | 99 | 10 | 25 | 11.5 | 65 | 188 | 15 | 2.6 |
| 502100601000670 | 6 FHSX | 6 | 0-100 | 220 | 145 | 25 | 30.5 | 19.5 | 120 | 414 | 20 | 16.5 |
| 502100801000670 | 8 FHSX | 8 | 0-100 | 225 | 135 | 35 | 30.5 | 19.5 | 120 | 428 | 30 | 21 |

Blueprint

